



# Quantity Estimate Sheet

<b>Petrolatum Tapes</b>	<b>Tape Width in (mm)</b>	<b>Tape Length ft (m)</b>	<b>Rolls Per Case</b>	<b>Coverage w/ 1" (25 mm) Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>	<b>Coverage w/ 55% Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>
<b>Premtape Tropical</b>	2 (50)	33 (10)	36	87 (8)	87 (8)
<b>Premtape LT</b>	4 (100)	33 (10)	18	145 (13.4)	87 (8)
<b>Premtape Hi-Heat Tape</b>	6 (150)	33 (10)	12	162 (15)	87 (8)
<b>Prembond Hi-Tack Tape</b>	8 (200)	33 (10)	8	150 (14)	77 (7)
<b>Prembond Colorflex Tape</b>	2 (50)	25 (7.6)	24	45 (4)	45 (4)
	4 (100)	25 (7.6)	12	74 (6.8)	45 (4)
	6 (150)	25 (7.6)	8	83 (7.71)	45 (4)
	8 (200)	25 (7.6)	8	116 (10.7)	60 (5.5)
	12 (300)	25 (7.6)	4	91 (8.4)	45 (4)

<b>Protective Outerwraps</b>	<b>Tape Width in (mm)</b>	<b>Tape Length ft (m)</b>	<b>Rolls Per Case</b>	<b>Coverage w/ 1" (25 mm) Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>	<b>Coverage w/ 55% Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>
<b>Premcote Glass Outerwrap</b>	3 (75)	9 (2.7)	15	—	17 (1.6)
	4 (100)	30 (10)	5	—	25 (2.3)
	8 (200)	40 (12)	3	—	40 (3.7)
<b>Premcote Glass Outerwrap HD</b>	8 (200)	40 (12)	10	—	133 (12.3)
<b>Premcote Glass Outerwrap UV</b>	3 (75)	9 (2.7)	100	—	113 (10.7)
	4 (100)	30 (10)	40	—	200 (18.4)
	8 (200)	40 (12)	15	—	200 (18.4)
<b>Viscotag PVC Outerwrap (10 MIL)</b>	2 (50)	100 (30)	24	200 (19)	200 (18.5)
	4 (100)	100 (30)	12	300 (28)	200 (18.5)
	6 (150)	100 (30)	8	333 (31)	200 (18.5)
<b>Viscotag PVC Outerwrap (20 MIL)</b>	4 (100)	100 (30)	9	225 (90)	150 (13.9)
	6 (150)	100 (30)	6	225 (90)	150 (13.9)
<b>Premier Poly-Wrap</b>	4 (100)	500 (125)	6	—	550 (51)
	6 (150)	500 (125)	4	—	550 (51)
	12 (300)	500 (125)	2	—	550 (51)

<b>Bitumen/Butyl Tapes</b>	<b>Tape Width in (mm)</b>	<b>Tape Length ft (m)</b>	<b>Rolls Per Case</b>	<b>Coverage w/ 1" (25 mm) Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>	<b>Coverage w/ 55% Overlap ft<sup>2</sup>/case (m<sup>2</sup>/case)</b>
<b>Premcote Butyl 30 Tape</b>	2 (50)	75 (23)	24	150 (14)	150 (14)
	4 (100)	75 (23)	12	225 (21)	150 (14)
	6 (150)	75 (23)	8	250 (23)	150 (14)
<b>Premcote Butyl 35 Tape</b>	2 (50)	50	24	100 (9.3)	100 (9.3)
	4 (100)	50	12	150 (14)	100 (9.3)
	6 (150)	50	8	167 (15.5)	100 (9.3)
<b>Premcote MB-50 Tape</b>	2 (50)	50	12	90 (8.3)	100 (9.3)
	4 (100)	50	6	150 (13.9)	100 (9.3)
	6 (150)	50	4	168 (15.6)	100 (9.3)
<b>Premcote 150R</b>	2 (50)	33 (10)	24	59 (5)	59 (5)
	4 (100)	33 (10)	12	99 (9)	59 (5)
	6 (150)	33 (10)	8	109 (10)	59 (5)
<b>Premtherm Tape</b>	2 (50)	50	12	45 (4)	45 (4)
	4 (100)	50	6	75 (7)	45 (4)
	6 (150)	50	4	82 (7.6)	45 (4)
	12 (300)	50	2	90 (8.4)	45 (4)

Primers	Coverage Per Case		Packaging Per Case	
	English	Metric	English	Metric
Prempaste	484 ft <sup>2</sup> 1,210 ft <sup>2</sup>	45 m <sup>2</sup> 112.5 m <sup>2</sup>	4 ea. 5.5 lb tubs 55 lb drums	4 ea. 2.5 kg tubs 25 kg drums
Prempaste S105 for dry & wet surfaces ▶ Primer for underwater applications ▶	484 ft <sup>2</sup> 220 ft <sup>2</sup> 1,210 ft <sup>2</sup>	45 m <sup>2</sup> 21 m <sup>2</sup> 112.5 m <sup>2</sup>	4 ea. 5.5 lb tubs 4 ea. 5.5 lb tubs 55 lb drums	4 ea. 2.5 kg tubs 4 ea. 2.5 kg tubs 25 kg drums
Prembond Hi-Tack Primer	1,076 ft <sup>2</sup>	100 m <sup>2</sup>	4 ea. 1.3 gal. containers	4 ea. 5 liter containers
Premcote Primer	1,822 ft <sup>2</sup>	169 m <sup>2</sup>	4 ea. 1 gal. containers	4 ea. 3.8 liter containers
Premcote P27	366 ft <sup>2</sup>	33 m <sup>2</sup>	6 ea. 1 quart containers	6 ea. 1 liter containers
	980 ft <sup>2</sup>	90 m <sup>2</sup>	4 ea. 1 gal. containers	4 ea. 3.8 liter containers

## Mastics

### Prembond Mastic

Pipe Diameter		Flanged Joint		Flanged Valve & Dresser Coupling	
in	mm	lbs	kg	lbs	kg
4	100	3.25	1.47	9.75	4.42
6	150	4.25	1.93	12.75	5.78
8	200	5.5	2.49	16.5	7.48
10	250	7	3.18	21	9.53
12	300	8.5	3.86	25.5	11.57
14	350	9.5	4.31	28.5	12.93
16	400	10.5	4.76	31.5	14.29
18	450	12	5.44	36	16.33
20	500	13	5.9	39	17.69
24	600	16	7.26	48	21.77
30	750	19	8.62	57	25.86

#### PACKAGING:

6 each 4 lb blocks = 24 lbs per case  
(6 each 1.75 kg blocks = 10.5 kg per case)

### Premier Molding Compound

Pipe Diameter		Flanged Joint		Flanged Valve		Dresser Coupling	
in	mm	lbs	kg	lbs	kg	lbs	kg
4	100	7	3.15	21	9.45	18	8.1
6	150	9	4.05	27	12.15	22	9.9
8	200	11	4.95	33	14.85	30	13.5
10	250	14	6.3	42	18.9	38	17.1
12	300	16	7.2	48	21.6	46	20.7
14	350	18	8.16	54	24.3	52	23.6
16	400	20	9	60	27	56	25.2
18	450	24	10.8	72	32.4	66	29.7
20	500	26	11.7	78	35.1	72	32.6
24	600	30	13.5	90	40.5	86	39
30	750	40	18	120	54	104	41.2

#### PACKAGING:

6 each 6.6 lb blocks = 39.6 lbs per case  
(6 each 3 kg blocks = 18 kg per case)

### Premier Molding Compound Blankets

Pipe Diameter		Flanged Joint	Flanged Valve	Dresser Coupling
in	mm	ea.	ea.	ea.
10	250	2	6	2
12	300	2.5	7.5	2.5
14	350	2.5	17.5	2.5
16	400	3	9	3
18	450	3.5	10.5	3
20	500	4	12	4
24	600	4.5	13.5	4
30	750	5	15	6
36	900	6	18	6
54	1350	12	36	12

#### PACKAGING:

5 each 10" x 39" = 44 lbs per case  
(5 each 250 mm x 1 m = 20 kg per case)



#### HOUSTON:

9710 Telge Road,  
Houston, Texas,  
U.S.A. 77095

Tel: 1-281-821-3355  
Fax: 1-281-821-0304

#### TORONTO:

90 Ironside Crescent,  
Unit 12, Toronto,  
Ontario, Canada M1X1M3

Tel: 1-416-291-3435  
Fax: 1-416-291-0898

e-mail: [info@premcoatings.com](mailto:info@premcoatings.com)

[www.premcoatings.com](http://www.premcoatings.com)

*A Member of Winn & Coales International*