

PREMCOTE PRIMER

Bitumen Tape Primer

Description

Premcote Primer is an oxidized bitumen in aromatic hydrocarbon solvents.

Uses

A fast drying bitumen based primer for all surfaces prior to the application of Premier bitumen tapes.

Features

- Fills surface irregularities for intimate contact of tape compound
- Promotes high adhesion
- Fast drying
- Good penetration characteristics
- Can be brush or spray applied

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Apply a thin uniform coat of Premcote Primer to clean surface and allow to tack dry. Drying time will be dependent on surface temperature.

Packaging

4 each 1 gallon containers per case (4 each 3.78 liter containers per case)



TECHNICAL DATA SHEET

Tech Data

Properties	Imperial	Metric
Specific Gravity	0.96	0.96
Drying Time	10 - 15 min @ 68°F	10 - 15 min @ 20°C
Flash Point	73°F	23°C
Maximum Service Temperature	170°F	77°C
*Coverage Capacity		
Per Container	455 ft ² /1 gallon	42 m ² /4 liters
Per Case	1820 ft ² /1 gallon	169 m ² /4 liters

**Note: Porous surfaces may yield less coverage*



HOUSTON:
9710 Telge Road,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.premcoatings.com

info@premcoatings.com

**A Member of Winn
& Coales International**

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.